


DS-HD6392MR-323C

H.265 2MP IR Dome IPC

DOWSE®

Product Picture:		Hardware		
		SOC	Hi3516CV300	
		Image Sensor	1/2.9" SONY EXMOR Progressive Scan CMOS SENSOR	
		Effective Pixels	1920(H)×1080(V)	
		Optical lens	Interfaces	φ 14
			Iris	Fixed Iris
			Focal Length	2.8-12mm(Manual)
		Audio Talkback		1ch MIC external access, 3.5mm AV interface
		Audio Output		1ch speaker output, 3.5mm AV interface
		Network Port	Lan	10/100M BASE-TX, RJ-45 connector
		RS485		1*RS485 interface
		Alarm I/O		2ch alarm input, 1ch alarm output
		Micro SD		Max. 128G
Product Features:		Audio&Video encoding		
◎ 1/2.9" SONY EXMOR Progressive Scan CMOS SENSOR ◎ 2.0 Megapixel, 30fps@1920*1080 ◎ 2.8-12mm(Manual), 3pcs IR Array LED for 30M, IR ON 0Lux, 120dB TWDR ◎ Support ONVIF Profile S, FTP, RTSP, UPnP etc. ◎ Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎ Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485、RJ45, DC 12V/AC 24V, POE		Video Compression	H.265/H.264/MJPEG	
			H.265 encoding: Main Profile	
			H.264 encoding: High Profile/Main Profile/Baseline	
		Resolution	Main Stream	1920*1080/1280*720; 1~30fps(adjustable)
			Sub Stream	704*576/640*480/640*352/320*240; 1~30fps(adjustable)
		Video Bitrate		30Kbps~16Mbps, Supports CBR/VBR
		OSD Settings		Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable
		Privacy Mask		4 configurable regions
		Image Orientation		Image Flip and Mirror
		Auto Image Control Functions		Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)
		Image Controls		Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR
		Others		Anti Fogging/Anti Trembling/IR Detection/IRIS/
		Audio Compression		G.711A/G.711U/G.726
		Two Way Audio		Support
Application Scenarios:		Data transmission and storage		
Supermarket, hotel, airport, office building etc.		Data storage	Video and Image	
		Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
		Alarm output	FTP, E-mail	
		Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
Order Type:		Wireless protocols(-W)		
DS-HD6392MR-323C		ONVIF Protocols		PROFILE S
		Remote View	PC	IE 6.0 above, Firefox, Google etc.
			Mobile Phone	
			User Access	Maximum 5 users
Outline Dimension:		General Parameters		
		Environmental Casing		Aluminum Alloy Housing, Indoor Applicable
		Installation		Ceiling Mounted & Wall Mounted
		Operating Temperature		-10 °C ~ 50 °C
		Operating Humidity		0% -85% RH
		Power		DC12V ±10%(AC 24±10%)
		POE		Support
		Power Consumption		<3.5W, IR ON<9W
		Dimension		Φ137xH105mm
		Weight		675g



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdwse.com>