

DS-HD6392Z-185D

H.265 2MP Dome IPC

DOWSE®**Product Picture:****Hardware**

SOC		Hi3516D
Image Sensor		1/1.8" SONY EXMOR Progressive Scan CMOS SENSOR
Effective Pixels		1920(H)×1080(V)
Interface		
Optical lens	Interfaces	§ 14
	Iris	Fixed Iris
	Focal Length	3.6-10mm(Motorized & One Push)
Audio Talkback		1ch MIC external access, 3.5mm AV interface
Audio Output		1ch speaker output, 3.5mm AV interface
Network Port	Lan	10/100M BASE-TX, RJ-45 connector
RS485		1*RS485 interface
Alarm I/O		DS-HD6392Z-185D
Micro SD		Max. 128G

Product Features:

◎ 1/1.8" SONY EXMOR Progressive Scan CMOS SENSOR
 ◎ 2.0 Megapixel, 30fps@1920*1080
 ◎ 3.6-10mm(Motorized & One Push), 0.001lux, 120dB TWDR
 ◎ Support ONVIF Profile S, FTP, RTSP, UPnP etc.
 ◎ Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc.
 ◎ Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485、RJ45, DC 12V/AC 24V, POE

Audio&Video encoding

Video Compression	H.265/H.264/MJPEG	
	H.265 encoding: Main Profile	
	H.264 encoding: High Profile/Main Profile/Baseline	
Resolution	Main Stream	1920*1080/1280*720; 1~30fps(adjustable)
	Sub Stream	704*576/640*480/640*352/320*240; 1~30fps(adjustable)
Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR	
OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.	
	OSD location is adjustable	
Privacy Mask	4 configurable regions	
Image Orientation	Image Flip and Mirror	
Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)	
Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR	
Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/	
Audio Compression	G.711A/G.711U/G.726	
Two Way Audio	Support	

Application Scenarios:


Supermarket, hotel, airport, office building etc.

Data transmission and storage

Data storage	Video and Image
Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
Alarm output	FTP, E-mail
Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP

Order Type:

DS-HD6392Z-185D	Wireless protocols(-W)	
	ONVIF Protocols	
	Remote View	PC
		Mobile Phone
		User Access

Outline Dimension:**General Parameters**

Environmental Casing	Aluminum Alloy Housing, Indoor Applicable
Installation	Ceiling Mounted & Wall Mounted
Operating Temperature	-10 °C ~ 50 °C
Operating Humidity	0% -85% RH
Power	DC12V ±10%(AC 24±10%)
POE	Support
Power Consumption	<3.5W
Dimension	Φ137xH106mm
Weight	675g



深圳市东视电子有限公司
 SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
 Tel: +86-755-29500291 Fax: +86-755-29500160
 Web: <http://www.szdowse.com>