


Product Picture:	Hardware	
	SOC	Hi3516D
	Image Sensor	1/2.8" SONY EXMOR Progressive Scan CMOS SENSOR
	Effective Pixels	1920(H)×1080(V)
	Interface	
	Optical lens	Interfaces CS
		Iris Fixed Iris
		Focal Length 3.6mm
	Audio Talkback	1ch MIC external access, 3.5mm AV interface
	Audio Output	1ch speaker output, 3.5mm AV interface
	Network Port	1* M12 interface
Product Features:	Audio&Video encoding	
© 1/2.8" SONY EXMOR Progressive Scan CMOS SENSOR © 2.0 Megapixel, 30fps@1920*1080 © 3.6mm, 2pcs IR Array LED for 10M.IR ON 0Lux, 140dB TWDR © Support ONVIF Profile S, FTP, RTSP, UPnP etc. © Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. © Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485、RJ45, DC 12V/AC 24V, POE	Video Compression	H.265/H.264/MJPEG
		H.265 encoding: Main Profile
		H.264 encoding: High Profile/Main Profile/Baseline
	Resolution	Main Stream 1920*1080/1280*720; 1~30fps(adjustable)
		Sub Stream 704*576/640*480/640*352/320*240; 1~30fps(adjustable)
	Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR
	OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.
		OSD location is adjustable
	Privacy Mask	4 configurable regions
	Image Orientation	Image Flip and Mirror
	Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)
	Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR
	Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/
	Audio Compression	G.711A/G.711U/G.726
	Two Way Audio	Support
Application Scenarios:	Data transmission and storage	
Supermarket, hotel, airport, office building etc.	Data storage	Video and Image
	Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
	Alarm output	FTP, E-mail
	Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP
Order Type:	Wireless protocols(-W)	
DS-HD6202R-290D-M12	ONVIF Protocols	PROFILE S
	Remote View	PC IE 6.0 above, Firefox, Google etc.
		Mobile Phone
		User Access Maximum 5 users
Outline Dimension:	General Parameters	
	Environmental Casing	Aluminum Alloy Housing, Indoor Applicable
	Installation	Ceiling Mounted & Wall Mounted
	Operating Temperature	-10 °C ~ 50 °C
	Operating Humidity	0% -85% RH
	Power	DC12V ±10%(AC 24±10%)
	POE	Support
	Power Consumption	<5W
	Dimension	Φ107xH64mm
	Weight	480g

