


DS-AI6392Z-327-CV5

DOWSE®

Product Picture:		Hardware			
		SOC		Hi3516CV500	
		Image Sensor		1/2.8" Progressive Scan CMOS	
		Effective Pixels		1920(H)×1080(V)	
		Interface			
		Optical lens	Interfaces	φ 14	
			Iris	auto iris	
			Lens type	7-22mm	
		Audio Talkback		1ch MIC external access, 3.5mm AV interface(Optional)	
		Audio Output		1ch speaker output, 3.5mm AV interface(Optional)	
		Network	Lan	10/100M BASE-TX, RJ-45 connector	
		RS485		1*RS485 interface(Optional)	
		Alarm I/O		2ch alarm input, 1ch alarm output(Optional)	
		Micro SD		Micro SD, Max 128GB	
		Product Features:		Audio&Video encoding	
◎ 1/2.8" SONY Exmor CMOS ◎ 2.0 Megapixel, 30fps@1920*1080 ◎ 7-22(motorized&one push) lens, 0.01 Lux,140dB TWDR ◎ Face capture algorithm (supports face capture function, supports detection, capture, screening, and output of optimal face capture) ◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP.UPNP etc. ◎Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎built-in Mic, Support Audio I/O, dual Alarm in/ single Alarm in out, RS485, SD card slot(128G), RJ45,DC 12V/AC 24V,PoE,		Video Compression		H.264/H.265/MJPEG	
				H.265 Coding type: Main Profile	
				H.264 Coding type: BaseLine Profile / Main Profile	
		Resolution	Main Stream	1920*1080/1280*720 1~60fps(adjustable)	
			Sub Stream	704*576/640*480/640*352/320*240 1~60fps(adjustable)	
		Video Bitrate		30Kbps~16Mbps(adjustable); Supports CBR/VBR	
		OSD Settings		Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable	
		Privacy Mask		4 configurable regions	
		Image Orientation		Image Flip and Mirror	
		Auto Image Control Functio		Auto Exposure Control (AEC); Auto White Blance (AWB); Auto	
		Image Controls		Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-	
		Others		Anti Fogging/Anti Trembling/IR Detection/IRIS/	
		Audio Compression		G.711A/G.711U/G.726	
		Two Way Audio		Support	
Application Scenarios:		Network features			
This product is widely used in shopping malls, hotels, airports, office buildings and other indoor places."		Data storage		Video/image	
		Recording		Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
		Alarm output		FTP, E-mail	
		Network protocols		TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
Order Type:		Wireless protocols(-W)		-----	
DS-AI6392Z-327-CV5		ONVIF protocol		PROFILE S	
		Remote View	PC	IE 6.0 above, Firefox, Google etc.	
			Mobile Phone		
		User Access	Maximum 5 users		
Outline Dimension:		General Parameters			
		Environmental Casing		Aluminum Alloy Housing, Indoor Applicable	
		Installation		Ceiling Mounted & Wall Mounted,	
		Operating Temperature		-10 °C ~ 50 °C	
		Operating Humidity		0% -85% RH	
		Power		DC12V±10% (AC 24±10%)	
		POE		support	
		Power Consumption		<3.5W	
		Dimension		Φ137.3xH106mm	
		Weight		735g	



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdwse.com>