


DS-HD6502R-229D

Pantograph HD IPC

DOWSE®

Product Picture:	Hardware	
	SOC	Hi3516D
	Image Sensor	1/3" Progressive Scan CMOS
	Effective Pixels	1920(H)×1080(V)
	Interface	
	Optical lens	Interfaces CS
		Iris Fixed Iris
		Focal Length 2.8mm
	Audio Talkback	1ch MIC external access, 3.5mm AV interface
	Audio Output	1ch speaker output, 3.5mm AV interface
	Network Port	Lan 10/100M BASE-TX, RJ-45 connector
Product Features:	Audio&Video encoding	
◎ 1/3" Progressive Scan CMOS ◎ 2.0 Megapixel, 30fps@1920*1080 ◎ 2.8-12mm(Manual), 24pcs IR Array LED for 15M.IR ON 0Lux, 140dB TWDR ◎ Support ONVIF Profile S, FTP, RTSP, UPnP etc. ◎ Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎ Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485、RJ45, DC 12V/AC 24V, POE	Video Compression	H.265/H.264/MJPEG
		H.265 encoding: Main Profile
		H.264 encoding: High Profile/Main Profile/Baseline
	Resolution	Main Stream 1920*1080/1280*720; 1~30fps(adjustable)
		Sub Stream 704*576/640*480/640*352/320*240; 1~30fps(adjustable)
	Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR
	OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.
		OSD location is adjustable
	Privacy Mask	4 configurable regions
	Image Orientation	Image Flip and Mirror
	Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)
	Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR
	Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/
	Audio Compression	G.711A/G.711U/G.726
	Two Way Audio	Support
Application Scenarios:	Data transmission and storage	
Supermarket, hotel, airport, office building etc.	Data storage	Video and Image
	Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
	Alarm output	FTP, E-mail
	Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP
Order Type:	Wireless protocols(-W)	
DS-HD6502R-229D	ONVIF Protocols	PROFILE S
	Remote View	PC IE 6.0 above, Firefox, Google etc.
		Mobile Phone
		User Access Maximum 5 users
Outline Dimension:	General Parameters	
	Environmental Casing	Aluminum Alloy Housing, Indoor Applicable
	Installation	Ceiling Mounted & Wall Mounted
	Operating Temperature	-10 °C ~ 50 °C
	Operating Humidity	0% -85% RH
	Power	DC12V ±10%(AC 24±10%)
	POE	Support
	Power Consumption	<3.5W
	Dimension	Φ143xH114mm
	Weight	655g



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdowse.com>