


DS-HD6392M-290D

H.265 2MP Dome IPC

DOWSE®

Product Picture:		Hardware	
		SOC	Hi3516D
		Image Sensor	1/2.8" SONY EXMOR Progressive Scan CMOS SENSOR
		Effective Pixels	1920(H)×1080(V)
		Interface	
		Optical lens	Interfaces ϕ 14
			Iris Fixed Iris
			Focal Length 3.6-10mm(Manual)
		Audio Talkback	1ch MIC external access, 3.5mm AV interface
		Audio Output	1ch speaker output, 3.5mm AV interface
		Network Port	Lan 10/100M BASE-TX, RJ-45 connector
		RS485	1*RS485 interface
Product Features:		Alarm I/O	2ch alarm input, 1ch alarm output
© 1/2.8" SONY EXMOR Progressive Scan CMOS SENSOR © 2.0 Megapixel, 30fps@1920*1080 © 3.6-10mm(Manual), 3pcs IR Array LED for 30M, 0.005Lux, 120dB TWDR © Support ONVIF Profile S, FTP, RTSP, UPnP etc. © Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. © Built-in MIC, Audio I/O, Dual Alarm In, Single Alarm Out, SD card slot(Max. 128G), RS485, RJ45, DC 12V/AC 24V, POE		Micro SD	Max. 128G
		Audio&Video encoding	
		Video Compression	H.265/H.264/MJPEG
			H.265 encoding: Main Profile
			H.264 encoding: High Profile/Main Profile/Baseline
		Resolution	Main Stream 1920*1080/1280*720; 1~30fps(adjustable)
			Sub Stream 704*576/640*480/640*352/320*240; 1~30fps(adjustable)
		Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR
		OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.
			OSD location is adjustable
		Privacy Mask	4 configurable regions
		Image Orientation	Image Flip and Mirror
		Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)
		Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR
		Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/
		Audio Compression	G.711A/G.711U/G.726
		Two Way Audio	Support
Application Scenarios:		Data transmission and storage	
Supermarket, hotel, airport, office building etc.		Data storage	Video and Image
		Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
		Alarm output	FTP, E-mail
		Network protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
Order Type:		Wireless protocols(-W)	
DS-HD6392M-290D		ONVIF Protocols	PROFILE S
		Remote View	PC IE 6.0 above, Firefox, Google etc.
			Mobile Phone
			User Access Maximum 5 users
Outline Dimension:		General Parameters	
		Environmental Casing	Aluminum Alloy Housing, Indoor Applicable
		Installation	Ceiling Mounted & Wall Mounted
		Operating Temperature	-10 °C ~ 50 °C
		Operating Humidity	0% -85% RH
		Power	DC12V ±10%(AC 24±10%)
		POE	Support
		Power Consumption	<3.5W, IR ON<9W
		Dimension	Φ137xH105mm
		Weight	675g



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdownse.com>