


DS-AI6002-327-CV5

DOWSE®

Product Picture:		Hardware		
		SOC	Hi3516CV500	
		Image Sensor	1/2.8" Progressive Scan CMOS	
		Effective Pixels	1920(H)×1080(V)	
		Interface		
		Optical lens	Interfaces	CS
			Iris	-----
			Focal Length	-----
		Audio Talkback	1ch MIC external access, 3.5mm AV interface(Optional)	
		Audio Output	1ch speaker output, 3.5mm AV interface(Optional)	
		Network	Lan	10/100M BASE-TX, RJ-45 connector
RS485		1*RS485 interface(Optional)		
Alarm I/O		1ch alarm input, 1ch alarm output(Optional)		
Micro SD		Micro SD, Max 128GB		
Product Features:		Audio&Video encoding		
◎ 1/2.8" SONY Exmor CMOS ◎ 2.1 Megapixel, 60fps@1920*1080 ◎ C/CS lens, 0.01 Lux, 140dB TWDR ◎ Face capture algorithm (supports face capture function, supports detection, capture, screening, and output of optimal face capture) ◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP.UPNP etc. ◎Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎Support Audio I/O, dual Alarm in/ single Alarm in out, RS485, PoE, SD card slot(128G), RJ45,DC 12V/AC 24V		Video Compression	H.264/H.265/MJPEG	
			H.265 Coding type: Main Profile	
			H.264 Coding type: BaseLine Profile / Main Profile	
		Resolution	Main Stream	1920*1080/1280*720 1~60fps(adjustable)
			Sub Stream	704*576/640*480/640*352/320*240 1~60fps(adjustable)
		Video Bitrate	30Kbps~16Mbps(adjustable); Supports CBR/VBR	
		OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable	
		Privacy Mask	4 configurable regions	
		Image Orientation	Image Flip and Mirror	
		Auto Image Control Functio	Auto Exposure Control (AEC); Auto White Blance (AWB); Auto	
		Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-	
		Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/	
		Audio Compression	G.711A/G.711U/G.726	
		Two Way Audio	Support	
		Application Scenarios:		Network features
This product is widely used in roads, plazas, schools, smart communities, prisons, military management areas, etc.		Data storage	Video/image	
		Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
		Alarm output	FTP, E-mail	
		Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP	
Order Type:		Wireless protocols(-W)		
DS-AI6002-327-CV5		ONVIF protocol	PROFILE S	
		Remote View	PC	IE 6.0 above, Firefox, Google etc.
			Mobile Phone	
			User Access	Maximum 5 users
Outline Dimension:		General Parameters		
		Environmental Casing	Aluminum Alloy Housing, Indoor Applicable	
		Installation	Ceiling Mounted & Wall Mounted, 3D adjustable	
		Operating Temperature	-10 °C ~ 50 °C	
		Operating Humidity	0% -85% RH	
		Power	DC12V±10%	
		POE	Optional	
		Power Consumption	<3W	
		Dimension	L142×W66×H68mm	
		Weight	599g	



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdownse.com>