

DS-AI8354Z-347-19A

DOWSE®

<div>Product Picture:</div> <div></div>	<div>Hardware</div> <table><tr><td>SOC</td><td>Hi3519A</td></tr><tr><td>Image Sensor</td><td>1/1.8" Progressive Scan CMOS</td></tr><tr><td>Effective Pixels</td><td>2560(H)×1440(V)</td></tr></table> <div>Interface</div> <table><tr><td rowspan="3">Optical lens</td><td>Interfaces</td><td>φ 14</td></tr><tr><td>Iris</td><td>fixed iris</td></tr><tr><td>Lens type</td><td>9-22mm(motorized)</td></tr><tr><td colspan="2">Audio Talkback</td><td>1ch MIC external access, 3.5mm AV interface(Optional)</td></tr><tr><td colspan="2">Audio Output</td><td>1ch speaker output, 3.5mm AV interface(Optional)</td></tr><tr><td>Network</td><td>Lan</td><td>10/100M BASE-TX, RJ-45 connector</td></tr><tr><td colspan="2">RS485</td><td>1*RS485 interface(Optional)</td></tr><tr><td colspan="2">Alarm I/O</td><td>2ch alarm input, 1ch alarm output(Optional)</td></tr><tr><td colspan="2">Micro SD</td><td>Micro SD, Max 128GB</td></tr></table>	SOC	Hi3519A	Image Sensor	1/1.8" Progressive Scan CMOS	Effective Pixels	2560(H)×1440(V)	Optical lens	Interfaces	φ 14	Iris	fixed iris	Lens type	9-22mm(motorized)	Audio Talkback		1ch MIC external access, 3.5mm AV interface(Optional)	Audio Output		1ch speaker output, 3.5mm AV interface(Optional)	Network	Lan	10/100M BASE-TX, RJ-45 connector	RS485		1*RS485 interface(Optional)	Alarm I/O		2ch alarm input, 1ch alarm output(Optional)	Micro SD		Micro SD, Max 128GB								
SOC	Hi3519A																																							
Image Sensor	1/1.8" Progressive Scan CMOS																																							
Effective Pixels	2560(H)×1440(V)																																							
Optical lens	Interfaces	φ 14																																						
	Iris	fixed iris																																						
	Lens type	9-22mm(motorized)																																						
Audio Talkback		1ch MIC external access, 3.5mm AV interface(Optional)																																						
Audio Output		1ch speaker output, 3.5mm AV interface(Optional)																																						
Network	Lan	10/100M BASE-TX, RJ-45 connector																																						
RS485		1*RS485 interface(Optional)																																						
Alarm I/O		2ch alarm input, 1ch alarm output(Optional)																																						
Micro SD		Micro SD, Max 128GB																																						
<div>Product Features:</div> <div><div>◎ 1/1.8" SONY Exmor CMOS</div><div>◎ 4.0 Megapixel, 30fps@1920*1080</div><div>◎ 9-22(motorized&one push) lens, 2 array led for 60M, IR ON 0Lux,140dB TWDR</div><div>◎ Face matching algorithm (supports face capture function, can detect and capture 30 faces at the same time; support front-end face matching, support up to 3 face database management, support import of up to 90,000 faces)</div><div>◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP.UPNP etc.</div><div>◎Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc.</div><div>◎ Support RJ45, DC 12V, Bracket integrated design;</div><div>◎option: Audio I/O, Alarm I/O,SD slot, RS485, POE</div></div>	<div>Audio&Video encoding</div> <table><tr><td rowspan="3">Video Compression</td><td colspan="2">H.264/H.265/MJPEG</td></tr><tr><td colspan="2">H.265 Coding type: Main Profile</td></tr><tr><td colspan="2">H.264 Coding type: BaseLine Profile / Main Profile</td></tr><tr><td rowspan="2">Resolution</td><td>Main Stream</td><td>1920*1080/1280*720 1~60fps(adjustable)</td></tr><tr><td>Sub Stream</td><td>704*576/640*480/640*352/320*240 1~60fps(adjustable)</td></tr><tr><td colspan="2">Video Bitrate</td><td>30Kbps~16Mbps(adjustable); Supports CBR/VBR</td></tr><tr><td colspan="2">OSD Settings</td><td>Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable</td></tr><tr><td colspan="2">Privacy Mask</td><td>4 configurable regions</td></tr><tr><td colspan="2">Image Orientation</td><td>Image Flip and Mirror</td></tr><tr><td colspan="2">Auto Image Control Functio</td><td>Auto Exposure Control (AEC); Auto White Blance (AWB); Auto</td></tr><tr><td colspan="2">Image Controls</td><td>Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-</td></tr><tr><td colspan="2">Others</td><td>Anti Fogging/Anti Trembling/IR Detection/IRIS/</td></tr><tr><td colspan="2">Audio Compression</td><td>G.711A/G.711U/G.726</td></tr><tr><td colspan="2">Two Way Audio</td><td>Support</td></tr></table>	Video Compression	H.264/H.265/MJPEG		H.265 Coding type: Main Profile		H.264 Coding type: BaseLine Profile / Main Profile		Resolution	Main Stream	1920*1080/1280*720 1~60fps(adjustable)	Sub Stream	704*576/640*480/640*352/320*240 1~60fps(adjustable)	Video Bitrate		30Kbps~16Mbps(adjustable); Supports CBR/VBR	OSD Settings		Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable	Privacy Mask		4 configurable regions	Image Orientation		Image Flip and Mirror	Auto Image Control Functio		Auto Exposure Control (AEC); Auto White Blance (AWB); Auto	Image Controls		Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-	Others		Anti Fogging/Anti Trembling/IR Detection/IRIS/	Audio Compression		G.711A/G.711U/G.726	Two Way Audio		Support
Video Compression	H.264/H.265/MJPEG																																							
	H.265 Coding type: Main Profile																																							
	H.264 Coding type: BaseLine Profile / Main Profile																																							
Resolution	Main Stream	1920*1080/1280*720 1~60fps(adjustable)																																						
	Sub Stream	704*576/640*480/640*352/320*240 1~60fps(adjustable)																																						
Video Bitrate		30Kbps~16Mbps(adjustable); Supports CBR/VBR																																						
OSD Settings		Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable																																						
Privacy Mask		4 configurable regions																																						
Image Orientation		Image Flip and Mirror																																						
Auto Image Control Functio		Auto Exposure Control (AEC); Auto White Blance (AWB); Auto																																						
Image Controls		Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-																																						
Others		Anti Fogging/Anti Trembling/IR Detection/IRIS/																																						
Audio Compression		G.711A/G.711U/G.726																																						
Two Way Audio		Support																																						
<div>Application Scenarios:</div> <div>This product is widely used in government agencies, intelligent communities, hospitals, roads, transportation, schools, prisons, military management and other places."</div>	<div>Network features</div> <table><tr><td>Data storage</td><td>Video/image</td></tr><tr><td>Recording</td><td>Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)</td></tr><tr><td>Alarm output</td><td>FTP, E-mail</td></tr><tr><td>Network protocols</td><td>TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP</td></tr></table>	Data storage	Video/image	Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	Alarm output	FTP, E-mail	Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP																															
Data storage	Video/image																																							
Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)																																							
Alarm output	FTP, E-mail																																							
Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP																																							
<div>Order Type:</div> <div>DS-AI8354Z-347-19A</div>	<div>Wireless protocols(-W)</div> <div>-----</div> <div>ONVIF protocol</div> <div>PROFILE S</div> <table><tr><td rowspan="3">Remote View</td><td>PC</td><td>IE 6.0 above, Firefox, Google etc.</td></tr><tr><td>Mobile Phone</td><td></td></tr><tr><td>User Access</td><td>Maximum 5 users</td></tr></table>	Remote View	PC	IE 6.0 above, Firefox, Google etc.	Mobile Phone		User Access	Maximum 5 users																																
Remote View	PC		IE 6.0 above, Firefox, Google etc.																																					
	Mobile Phone																																							
	User Access	Maximum 5 users																																						
<div>Outline Dimension:</div> <div></div>	<div>General Parameters</div> <table><tr><td>Environmental Casing</td><td>Aluminum Alloy Housing, Indoor Applicable</td></tr><tr><td>Installation</td><td>Ceiling Mounted & Wall Mounted,</td></tr><tr><td>Operating Temperature</td><td>-10 °C ~ 50 °C</td></tr><tr><td>Operating Humidity</td><td>0% -85% RH</td></tr><tr><td>Power</td><td>DC12V±10% (AC 24±10%)</td></tr><tr><td>POE</td><td>support</td></tr><tr><td>Power Consumption</td><td><12W</td></tr><tr><td>Dimension</td><td>L310XW100XH70mm</td></tr><tr><td>Weight</td><td>965g</td></tr></table>	Environmental Casing	Aluminum Alloy Housing, Indoor Applicable	Installation	Ceiling Mounted & Wall Mounted,	Operating Temperature	-10 °C ~ 50 °C	Operating Humidity	0% -85% RH	Power	DC12V±10% (AC 24±10%)	POE	support	Power Consumption	<12W	Dimension	L310XW100XH70mm	Weight	965g																					
Environmental Casing	Aluminum Alloy Housing, Indoor Applicable																																							
Installation	Ceiling Mounted & Wall Mounted,																																							
Operating Temperature	-10 °C ~ 50 °C																																							
Operating Humidity	0% -85% RH																																							
Power	DC12V±10% (AC 24±10%)																																							
POE	support																																							
Power Consumption	<12W																																							
Dimension	L310XW100XH70mm																																							
Weight	965g																																							



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdownse.com>