


DS-AI6392Z-385-19A

DOWSE®

Product Picture: 	Hardware						
	SOC		Hi3519A				
	Image Sensor		1/1.8" Progressive Scan CMOS				
	Effective Pixels		1920(H)×1080(V)				
	Interface						
	Optical lens	Interfaces	φ 14				
		Iris	auto iris				
		Lens type	3.6-10mm				
	Audio Talkback		1ch MIC external access, 3.5mm AV interface(Optional)				
	Audio Output		1ch speaker output, 3.5mm AV interface(Optional)				
	Network	Lan	10/100M BASE-TX, RJ-45 connector				
	RS485		1*RS485 interface(Optional)				
	Alarm I/O		2ch alarm input, 1ch alarm output(Optional)				
	Micro SD		Micro SD, Max 128GB				
	Product Features:						
◎ 1/1.8" SONY Exmor CMOS ◎ 2.0 Megapixel, 30fps@1920*1080 ◎ 3.6-10(motorized&one push) lens, 0.001 Lux,120dB TWDR ◎ Face matching algorithm (supports face capture function, can detect and capture 30 faces at the same time; support front-end face matching, support up to 3 face database management, support import of up to 90,000 faces) ◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP.UPNP etc. ◎Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎built-in Mic, Support Audio I/O, dual Alarm in/ single Alarm in out, RS485, SD card slot(128G), RJ45,DC 12V/AC 24V,PoE,							
				Audio&Video encoding			
				Video Compression		H.264/H.265/MJPEG	
						H.265 Coding type: Main Profile	
				Resolution		H.264 Coding type: BaseLine Profile / Main Profile	
						Main Stream	1920*1080/1280*720 1~60fps(adjustable)
				Sub Stream		704*576/640*480/640*352/320*240 1~60fps(adjustable)	
						Video Bitrate	
				OSD Settings		30Kbps~16Mbps(adjustable); Supports CBR/VBR	
				Privacy Mask		Text overlay supported like title, time, date, week, bitrate and etc.	
						OSD location is adjustable	
				Image Orientation		4 configurable regions	
				Image Orientation		Image Flip and Mirror	
				Auto Image Control Functio		Auto Exposure Control (AEC); Auto White Blance (AWB); Auto	
				Image Controls		Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-	
Others		Anti Fogging/Anti Trembling/IR Detection/IRIS/					
Audio Compression		G.711A/G.711U/G.726					
Two Way Audio		Support					
Application Scenarios:							
This product is widely used in shopping malls, hotels, airports, office buildings and other indoor places."							
				Network features			
				Data storage		Video/image	
				Recording		Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)	
				Alarm output		FTP, E-mail	
Network protocols		TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、HTTPS、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP					
Order Type:							
DS-AI6392Z-385-19A							
				Wireless protocols(-W)			
				ONVIF protocol			
				PROFILE S			
				Remote View	PC	IE 6.0 above, Firefox, Google etc.	
Mobile Phone							
User Access	Maximum 5 users						
Outline Dimension:							
							
				General Parameters			
				Environmental Casing		Aluminum Alloy Housing, Indoor Applicable	
				Installation		Ceiling Mounted & Wall Mounted,	
				Operating Temperature		-10 °C ~ 50 °C	
				Operating Humidity		0% -85% RH	
				Power		DC12V±10% (AC 24±10%)	
				POE		support	
				Power Consumption		<3.5W	
				Dimension		Φ137.3xH106mm	
Weight		735g					



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdownse.com>