

DS-AI8352Z-385-DV3

DOWSE®

Product Picture:		Hardware	
		SOC	Hi3516DV500
		Image Sensor	1/1.8" Progressive Scan CMOS
		Effective Pixels	1920(H)×1080(V)
		Interface	
		Optical lens	Interfaces ϕ 14
			Iris fixed iris
			Lens type 9-22mm(motorized)
		Audio Talkback	1ch MIC external access, 3.5mm AV interface(Optional)
		Audio Output	1ch speaker output, 3.5mm AV interface(Optional)
		Network	Lan 10/100M BASE-TX, RJ-45 connector
Product Features:		RS485	1*RS485 interface(Optional)
◎ 1/1.8" SONY Exmor CMOS ◎ 2.0 Megapixel, 30fps@1920*1080 ◎ 9-22(motorized&one push) lens, 2 array led for 60M, 0 Lux,140dB TWDR ◎ Face matching algorithm (supports face capture function, can detect and capture 30 faces at the same time; support front-end face matching, support up to 3 face database management, support import of up to 90,000 faces) ◎ Support protocols: PROFILE S, GB/T28181, FTP/RTSP.UPNP etc. ◎ Support three Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc. ◎ Support RJ45, DC 12V, Bracket integrated design; ◎ option: Audio I/O, Alarm I/O, SD slot, RS485, POE		Alarm I/O	2ch alarm input, 1ch alarm output(Optional)
		Micro SD	Micro SD, Max 128GB
		Audio&Video encoding	
		Video Compression	H.264/H.265/MJPEG
			H.265 Coding type: Main Profile
			H.264 Coding type: BaseLine Profile / Main Profile
		Resolution	Main Stream 1920*1080/1280*720 1~60fps(adjustable)
			Sub Stream 704*576/640*480/640*352/320*240 1~60fps(adjustable)
		Video Bitrate	30Kbps~16Mbps(adjustable); Supports CBR/VBR
		OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc. OSD location is adjustable
		Privacy Mask	4 configurable regions
		Image Orientation	Image Flip and Mirror
		Auto Image Control Function	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto
		Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-
		Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/
		Audio Compression	G.711A/G.711U/G.726
Application Scenarios:		Two Way Audio	Support
This product is widely used in government agencies, intelligent communities, hospitals, roads, transportation, schools, prisons, military management and other places."		Network features	
		Data storage	Video/image
		Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
		Alarm output	FTP, E-mail
		Network protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
Order Type:		Wireless protocols(-W)	-----
DS-AI8352Z-385-DV3		ONVIF protocol	PROFILE S
		Remote View	PC IE 6.0 above, Firefox, Google etc.
			Mobile Phone
			User Access Maximum 5 users
Outline Dimension:		General Parameters	
		Environmental Casing	Aluminum Alloy Housing, Indoor Applicable
		Installation	Ceiling Mounted & Wall Mounted,
		Operating Temperature	-10 °C ~ 50 °C
		Operating Humidity	0% -85% RH
		Power	DC12V±10% (AC 24±10%)
		POE	support
		Power Consumption	<12W
		Dimension	L310XW100XH70mm
		Weight	965g



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua
New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdownse.com>