

DS-HD8632M-229D

2.0MP HD IR WATERPROOF IP CAMERA

DOWSE®

Product Picture:



Hardware

SOC		Hi3516D
Image Sensor		1/3" Progressive Scan CMOS
Effective Pixels		1920(H)×1080(V)
Interface		
Optical lens	Interfaces	φ 14
	Iris	Fixed Iris
	Focal Length	2.8-12mm(Manual)
Audio Talkback		1ch MIC external access, 3.5mm AV interface (Optional)
Audio Output		1ch speaker output, 3.5mm AV interface (Optional)
Network Port	Lan	10/100M BASE-TX, RJ-45 connector
RS485		1*RS485 interface (Optional)
Alarm I/O		1ch alarm input, 1ch alarm output (Optional)
Micro SD		Max. 128G (Optional)

Product Features:

- ◎ 1/3" Progressive Scan CMOS
- ◎ 2.0 Megapixel, 30fps@1920*1080
- ◎ 2.8-12mm(Manual), 2pcs IR Array LED for 60M, IR ON 0Lux, 140dB TWDR
- ◎ Support ONVIF Profile S, FTP, RTSP, UPnP etc.
- ◎ Support Dual-Stream, Mobile Surveillance, Heartbeat Mechanism, 3D-DNR, Defogging, D-WDR, Lens Correction, Corridor Monitoring etc.
- ◎ RJ45, DC 12V, Easy-to-install bracket included
- ◎ Option: SD card slot, Alarm I/O, Audio I/O, RS485, POE

Audio&Video encoding

Video Compression	H.265/H.264/MJPEG	
	H.265 encoding: Main Profile	
	H.264 encoding: High Profile/Main Profile/Baseline	
Resolution	Main Stream	1920*1080/1280*720; 1~30fps(adjustable)
	Sub Stream	704*576/640*480/640*352/320*240; 1~30fps(adjustable)
Video Bitrate	30Kbps~16Mbps, Supports CBR/VBR	
OSD Settings	Text overlay supported like title, time, date, week, bitrate and etc.	
	OSD location is adjustable	
Privacy Mask	4 configurable regions	
Image Orientation	Image Flip and Mirror	
Auto Image Control Functions	Auto Exposure Control (AEC); Auto White Balance (AWB); Auto Gain Control(AGC)	
Image Controls	Saturation, Brightness, Contrast, Hue, Sharpness, Gamma, D-WDR	
Others	Anti Fogging/Anti Trembling/IR Detection/IRIS/	
Audio Compression	G.711A/G.711U/G.726	
Two Way Audio	Support	

Application Scenarios:

Government, intelligent community, hospital, road, transportation, school, prison, military district etc.

Data transmission and storage

Data storage	Video and Image
Recording	Auto recording and manual recording (motion & sensor alarm recording, scheduled recording)
Alarm output	FTP, E-mail
Network protocols	TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP


Order Type:

Wireless protocols(-W)

DS-HD8632M-229D

ONVIF Protocols		PROFILE S
Remote View	PC	IE 6.0 above, Firefox, Google etc.
	Mobile Phone	-----
	User Access	Maximum 5 users

Outline Dimension:



General Parameters

Environmental Casing	Aluminum Alloy Housing, Indoor and Outdoor Applicable
Installation	Ceiling Mounted & Wall Mounted
Operating Temperature	-10 °C ~ 50 °C
Operating Humidity	0% -85% RH
Power	DC12V ±10%(AC 24±10%)
POE	Support
Power Consumption	<12w(IR ON)
Dimension	L310XW100XH70mm
Weight	965g



深圳市东视电子有限公司
SHENZHEN DOWSE ELECTRONICS CO.,LTD.

Add: 3-4F, 9Building, Jinxiu Culture Technology Mall, Guanhu AVE, Longhua New District, Shenzhen, China
Tel: +86-755-29500291 Fax: +86-755-29500160
Web: <http://www.szdowse.com>